

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.

WHAT IS CLAIMED IS:

1. A diffractive optical element having plural diffraction grating surfaces accumulated, characterized in that: a pair of diffraction grating surfaces are positioned so that a protrusion and/or a recess formed on an outside of one diffraction grating surface engages with a recess and/or a protrusion formed on an outside of the other diffraction grating surface; and that the pair of diffraction grating surfaces are defined on materials having different refractive indices and different dispersions and being formed into a kinoform, or a shape and a height of blazed or binary, close to it, such that a largest optical path difference to be applied to light rays passing through the diffraction grating surfaces with respect to plural wavelengths becomes equal to a multiple, by an integral number, of the wavelength.

2. A diffractive optical element having plural diffraction grating surfaces accumulated, characterized in that: a pair of diffraction grating surfaces are positioned so that a protrusion and/or a recess formed outside an optically effective region of one diffraction grating surface engages with a recess and/or a protrusion formed outside an optically effective region of the other diffraction grating surface; and that the pair of diffraction grating

[illegible]

5

10

15

20

25

4. A diffractive optical element having plural

Sub  
C1  
CONF

5 diffraction grating surfaces accumulated,  
characterized in that: a pair of diffraction grating  
surfaces are positioned so that a protrusion and/or a  
recess formed outside an optically effective region of  
one diffraction grating surface engages with a recess  
and/or a protrusion formed outside an optically  
effective region of the other diffraction grating  
surface; and that the pair of diffraction grating  
surfaces are defined on materials having different  
10 refractive indices and different dispersions and being  
formed into a kinoform, or a shape and a height close  
to it, such that a diffraction efficiency of  
diffraction light of a particular order, such as one  
of positive and negative first order, with respect to  
15 plural wavelengths, becomes equal to or nearly equal  
to 100%.

5. A diffractive optical element according to  
any one of Claims 1 - 4, wherein the pair of  
20 diffraction gratings are disposed opposed to each  
other with a space such as by an air interposed  
therebetween.

25 6. A diffractive optical element according to  
any one of Claims 1 - 4, wherein the protrusion and  
the recess have a sectional shape of one of a triangle  
shape, a trapezoidal shape and a semi-circular shape.

7. A diffractive optical element having plural diffraction grating surfaces accumulated, characterized in that: a pair of diffraction grating surfaces are mutually positioned so that a protrusion and/or a recess having a sectional shape of one of a triangular shape, a trapezoidal shape, and a semi-circular shape, formed on one diffraction grating surface, engages with a recess and/or a protrusion having a sectional shape of one of a triangular shape, a trapezoidal shape, and a semi-circular shape, formed on the other diffraction grating surface.

8. A diffractive optical element having plural diffraction grating surfaces accumulated, characterized in that: a pair of diffraction grating surfaces are mutually positioned so that a protrusion and/or a recess having a sectional shape of one of a triangular shape, a trapezoidal shape, and a semi-circular shape, formed outside an optically effective region of one diffraction grating surface engages with a recess and/or a protrusion having a sectional shape of one of a triangular shape, a trapezoidal shape, and a semi-circular shape, formed outside an optically effective region of the other diffraction grating surface.

11. A method of manufacturing a diffractive optical element, comprising the steps of:

forming, upon a substrate, a first diffraction grating and a recess and/or a protrusion;

preparing a mold having a protrusion and/or a recess to be engaged with the recess and/or the protrusion formed on the substrate, as well as a second diffraction grating pattern; and

positioning the diffraction grating on the  
substrate and the diffraction grating pattern with  
each other by engaging the recess and/or the  
protrusion of the substrate with the protrusion and/or  
the recess of the mold.

5

12. An optical system having a diffractive  
optical element as manufactured in accordance with a  
method as recited in Claim 11.

10

13. An optical system having a diffractive  
optical element according to any one of Claims 1-4, 7 and 8.

15

14. An optical system having a diffractive  
optical element as manufactured in accordance with a  
method as recited in Claims 9 or 10.

20

25